

**IP | PNEUMATIC IMPACT WRENCHES**




**Industrial heavy duty design**

**Square drive sizes from 1/2" to 1 1/2"**


**Torque capacities up to 5933 Nm**

- ▶ Lightweight and compact design impact wrenches offering durability and reliability during operation
- ▶ Features twin hammer and 3-jaw hammer mechanism which offers increased power and balanced impact during bolt tightening
- ▶ Quiet operation and low vibration levels for reduced operator fatigue
- ▶ Ideal for use in applications in the automotive, construction, railways and heavy engineering industries as well as in tyre and mechanical workshops
- ▶ High quality impact sockets for use with IP range are listed on pages 85 and 86
- ▶ Filter, regulator & lubricator unit is recommended for use with IP impact wrenches

IP850 & IP1700



IP3200 & IP5950



Model number	Square drive size	Bolt range		Free speed R.P.M.	Maximum torque		Working pressure		Air inlet type	Vibration lvl (m/s <sup>2</sup> )	Sound pressure lvl db(a)	Weight (kg)	Dimensions (mm)			
		Metric	Imperial		Nm	lbf.ft	bar	psi					A	B	C	C Handle removed
Pistol grip versions																
IP850	1/2"	M10 - M16	3/8" - 5/8"	6000	850	627	6.5	94	1/4" NPT	8.6	93	2.5	175	186	65	No Handle
IP1700	3/4"	M14 - M24	9/16" - 1"	5400	1700	1254	6.3	92	1/2" BSP	9.4	102	5.9	221	250	184	96
IP1700X	3/4"	M14 - M24	9/16" - 1"	5400	1700	1254	6.3	92	1/2" BSP	9.4	102	6.6	252	250	184	96
Back handle grip versions																
IP3200	1"	M18 - M39	3/4" - 1 1/2"	3200	3185	2350	6.3	92	1/2" BSP	4.9	101	9.5	310	165	199	112
IP3200X	1"	M18 - M39	3/4" - 1 1/2"	3200	3185	2350	6.3	92	1/2" BSP	4.9	101	10.6	310	165	199	112
IP5950	1 1/2"	M24 - M56	1" - 2"	3200	5933	4376	6.3	92	1/2" BSP	12.3	104	14.5	371	166	213	124

Note: Models with suffix 'X' are fitted with extended anvil

Model number	Increase in anvil length (mm)
IP1700X	118.9
IP3200X	137



**FILTER REGULATOR LUBRICATOR (FRL) UNIT**



- ▶ Allows for easy adjustment of air pressure to suit tool requirements
- ▶ Prevents entry of contaminants and water into the air supply
- ▶ Supplied with dual scale air inlet pressure gauge and 3 meter air hose with swivel end fittings

Model number	Air inlet connection	Air outlet connection	Weight (kg)	Dimensions (mm)		
				Length	Width	Height
FRL11	1/2" NPT	1/2" NPT	3	200	200	310