

MANIFOLDS







Working pressure 700 Bar

Designed for single or double acting systems

2 or 4 outlet port models available

Hi-Force controlled manifold units are designed specifically to allow easy control of the direction of flow of the hydraulic fluid, within a single acting or double acting system. These controlled manifold units are mounted in a sturdy framework and are available as 2-outlet or 4-outlet options and are supplied with pressure gauges, reading 0-700 Bar, fitted to each outlet port. All models are fitted with quick connect couplings on all inlet and outlet ports, including the 2-Way and 4-Way open manifold return flow lines on double acting versions.



Model number	Type	Weight kg	Dimensions in mm			
			A	B	C	D
HM2C-SU	2-Way controlled manifold unit, suitable for single acting systems	2.0	150	51	51	100
HM2C-DU	2-Way controlled manifold unit, suitable for double acting systems	3.0	150	102	51	100
HM4C-SU	4-Way controlled manifold unit, suitable for single acting systems	3.5	350	51	51	100
HM4C-DU	4-Way controlled manifold unit, suitable for double acting systems	6.0	350	102	51	100

HYDRAULIC OIL

Hi-Force premium grade hydraulic oil is specially formulated for use with Hi-Force hydraulic tools, providing optimum performance throughout all working conditions.



Model number	Capacity litres	For use with
HFO32-1	1	Manually operated pumps
HFO32-5	5	Manually operated pumps
HFO32-25	25	Manually operated pumps
HFO46-1	1	Powered pumps
HFO46-5	5	Powered pumps
HFO46-25	25	Powered pumps